

APPROVED BY FORD - TOX # 186139



INDUSTRIAL OIL CONCENTRATE

HIGH-PERFORMANCE LUBRICANT FOR INDUSTRIAL APPLICATIONS

Using our proprietary XPL+ Technology, this extreme pressure formulation dramatically reduces friction, heat, and wear while remaining thermally stable. It adds superior performance to any oil application resulting in increased production efficiency and component life extension.



DIRECTIONS FOR USAGE:

- Use at 15% by total volume.
(For 75w-90 and lighter weight gear oils)



APPLICATIONS:

- Gear boxes
- Ball & roller bearings
- Pumps & Power Transmissions
- Heavy chains & sprockets
- Stamping
- Slitting machines
- Threading and dies
- Compressors, generators
- Ball & roller bearings

BOTTOM LINE BENEFITS

- High film strength
- Heavy load carrying capability
- Dramatically reduces friction, heat & wear
- Thermal stability over wide temperature range
- Provides oxidation stability
- Rust & corrosion inhibitor
- Built-in seal conditioners
- Compatible with seals and gaskets
- Eliminates gear housing chatter

ProOne#	Size	Case Pack
12001	1 gallon/3.785L	4
12005	5 gallon/18.9L Pail	1
12055	55 gallon/208L Drum	1